

0 601 231 101 – GOP 55-36

Material number	0 601 231 101	0 601 231 102
EAN	3165140816908	3165140875110
1 x Starlock BIM segmentni list testere ACZ 100 BB, Wood + Metal 2 608 661 633	✓	
1 x Starlock Carbide-RIFF brusna ploča AVZ 78 RT2, Grout + Abrasive 2 608 661 648	✓	
1 x Starlock Carbide-RIFF segmentni list testere ACZ 85 RT3, Grout + Abrasive 2 608 661 642	✓	
1 x Starlock delta brusna ploča AVZ 93 G 2 608 000 493	✓	✓
1 x StarlockMax BIM list testere za uranjanje MAII 52 APB, Curved-Tec, Wood + Metal 2 608 662 574	✓	
1 x StarlockMax BIM list testere za uranjanje MAIZ 32 APB, Curved-Tec, Wood + Metal 2 608 662 571	✓	✓
1 x StarlockMax Carbide list testere za uranjanje MAIZ 32 AT, Metal 2 608 662 567	✓	
1 x StarlockMax Carbide-RIFF list testere za uranjanje MATI 68 RT3, Grout + Abrasive 2 608 662 577	✓	
1 x StarlockMax HCS list testere za uranjanje MAII 32 SC, Multi Material 2 608 662 583	✓	
1 x StarlockMax HCS list testere za uranjanje MAIZ 32 EPC, Curved-Tec, Wood 2 608 662 568	✓	
25 x brusnih listova, K 10x80, 10x120, 5x240 2 608 621 105	✓	
5 x brusnih listova, K 2x80, 2x120, 1x240 2 608 621 104		✓
Kartonska kutija		✓
L-BOXX 136 1 600 A00 1RR	✓	
Starlock adapter za usisivač sa steznim vratom 2 608 000 636	✓	
Popust	0.0	0.0





Tehnički podaci

Tehnički podaci

Nominalna ulazna snaga	550 W
Broj oscilacija u praznom hodu	8.000 – 20.000 min ⁻¹
Ugao vibracije levo i desno	1,8 °
Težina	1,6 kg



Informacija o buci/vibraciji

Nivo zvučnog pritiska	81 dB(A)
Nivo zvučne snage	92 dB(A)
Nesigurnost K	3 dB

Segment

Segmenti	Paleta proizvoda za tešku primenu
----------	-----------------------------------

Informacije za prodaju

Positioning

- Veća primena - veća snaga!

User benefit

- Efikasan GOP, naročito robusan i snažan
- Alat kategorije StarlockMax za ekstremno napredak pri radu
- Snap In funkcija za izmenu pribora bez upotrebe pomagala u 3 sekunde