

0 601 9G3 40D – GWS 18V-10 SC

Material number	0 601 9G3 40D	0 601 9G3 40H	0 601 9G3 50B
EAN	3165140960885	3165140960915	3165140960922
1 x Bluetooth Low Energy modul GCY 30-4 1 600 A00 R26	✓	✓	
1 x akumulator GBA 18V 6.0Ah 1 600 A00 4ZN		✓	
1 x akumulator ProCORE18V 8.0Ah 1 600 A01 6GK		✓	
1/1 L-BOXX uložak za uređaj i punjač 1 600 A01 166	✓	✓	
2 x akumulatora GBA 18V 5.0Ah 1 600 A00 2U5	✓		
Brzi punjač GAL 1880 CV 1 600 A00 B8G	✓		
Brzi punjač GAL 18V-160 C Professional 1 600 A01 9S5		✓	
Brzostezna navrtka 2 608 000 684	✓	✓	✓
Dodatna drška sa kontrolom vibracija 2 602 025 171	✓	✓	✓
L-BOXX 136 1 600 A00 1RR	✓	✓	✓
Prihvatna prirubnica kataloški broj 2 605 703 014	✓	✓	✓
Štitnik 1 605 510 365	✓	✓	
Štitnik 1 605 510 366			✓
Brusna/rezna ploča, prečnik	125 mm	125 mm	150 mm
Napon akumulatora	18.0 V	18.0 V	18.0 V
Masa sa akumulatorom	2,8 kg	2,8 kg	2,8 kg
Popust	0.0	0.0	0.0
Broj obrtaja u praznom hodu			4.000 – 7.500 min-1





Tehnički podaci

Tehnički podaci

Broj obrtaja u praznom hodu	4.500 – 9.000 min-1
Napon akumulatora	18 V
Navoj brusnog vretena	M 14
Provrt, Ø	22,2 mm
Masa bez akumulatora	2 kg

Namenski alati

Brusna/rezna ploča, prečnik	125 mm
Gumeni brusni tanjir, prečnik	125 mm

Informacija o buci/vibraciji

Nivo zvučnog pritiska	79 dB(A)
Nivo zvučne snage	90 dB(A)
Nesigurnost K	3 dB

Segment

Segmenti	Paleta proizvoda za tešku primenu
----------	-----------------------------------



Informacije za prodaju

Positioning

- Napredni nivo snage i kontrola alata u kategoriji od 18 V